



TURISMO VELOCE 800 ROSSO

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.



AGO RED/METALLIC CARBON BLACK



* Top speed attained on closed course.

*** Available with and without EAS for the European market; only with EAS for the Extra European market.

Every country could have a price variation due to local import duties and taxes.

MY 2020 - 07/01/20

ENGINE	
Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C." with mechanical chain tensioner
Total displacement	798 cm ³ (48.7 cu. in.)
Compression ratio	12.3:1
Starting	Electric
Bore x stroke	79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)	81 kW (110 hp) at 10.150 r.p.m.
Max. torque - r.p.m.	80 Nm a 7.100 giri/min
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Integrated ignition - injection system MVICS 2.0 (Motor & Vehicle Integrated Control System) with three injectors. Engine control unit Eldor EM2.0, throttle body full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire. Torque control with four maps, Traction Control with eight levels of intervention with lean angle sensor
Electronic quick shift	MV EAS 2.1 (Electronically Assisted Shift Up & Down)***
Clutch	Hydraulic, wet, multi-disc with slipper clutch
Transmission	Cassette style; six speed, constant mesh
Primary drive	22/41
Gear ratio	
First gear:	13/37
Second gear:	16/35
Third gear:	18/32
Fourth gear:	20/30
Fifth gear:	22/29
Sixth gear:	21/25
Final drive ratio	16/41
ELECTRICAL EQUIPMENT	
Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 11 Ah
DIMENSIONS AND WEIGHT	
Wheelbase	1445 mm (56.89 in.)
Overall length	2125 mm (83.66 in.)
Overall width	910 mm (35.83 in.)
Saddle height	850 mm (33.46 in.)
Min. ground clearance	140 mm (5.51 in.)
Trail	108 mm (4.25 in.)
Dry weight	191 kg (421.1 lbs.)
Fuel tank capacity	21.5 l (5.68 U.S. gal.)
PERFORMANCE	
Maximum speed*	230 km/h (143 mph)

FRAME	
Type	ALS Steel tubular trellis (MAG welded)
Rear swing arm pivot plates material	Aluminium alloy
FRONT SUSPENSION	
Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	160 mm (6.30 in.)
REAR SUSPENSION	
Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	165 mm (6.50 in.)
BRAKES	
Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type, with 4 pistons Ø 32 mm (Ø 1.26 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Bosch 9 Plus with RLM (Rear wheel Lift-up Mitigation)
WHEELS	
Front: Material/size	Aluminium alloy 3.50" x 17"
Rear: Material/size	Aluminium alloy 6.00" x 17"
TYRES	
Front	120/70 - ZR 17 M/C (58 W)
Rear	190/55 - ZR 17 M/C (75 W)
FAIRING	
Material	Thermoplastic
ORIGINAL EQUIPMENT	
Included accessories	Immobilizer - Bluetooth - Cruise control Adjustable windshield
OPTIONAL	
	Garmin navigation system - GPS sensor Bags 34 l (8,98 U.S. gal. each) - Heated Grips Center stand
EMISSIONS	
Environmental Standard	Euro 4
Combined fuel consumption	5.8 l/100 km
CO ₂ Emissions	129 g/km

VISIT OUR WEBSITE TO SEE ALL THE AVAILABLE MV AGUSTA SPECIAL PARTS