



# SUPERVELOCE ALPINE



BLU ALPINE/AGO SILVER

E10 UNLEADED GASOLINE WITH UP TO 10% ETHANOL ONLY

## ENGINE

Type	Three cylinder, 4 stroke, 12 valve
Timing system	"D.O.H.C" with mechanical chain tensioner and DLC tappet
Total displacement	798 cm <sup>3</sup> (48.7 cu. in.)
Compression ratio	13.3:1
Starting	Electric
Bore x stroke	79 mm x 54.3 mm (3.1 in. x 2.1 in.)
Max. power - r.p.m. (at the crankshaft)	108 kW (147 hp) at 13.000 r.p.m. 112.5 kW (153 hp) at 13.250 r.p.m.**
Max. torque - r.p.m.	88 Nm (8.98 kgm) at 10.100 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Integrated ignition - injection system MVICS 2.1 (Motor & Vehicle Integrated Control System) with six injectors Engine control unit Eldor Nemo 2.1, throttle body full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire Torque control with four maps, Traction Control with eight levels of intervention
Electronic quick shift	MV EAS 3.0 (Electronically Assisted Shift Up & Down)
Clutch	Wet, multi-disc slipper clutch
Transmission	Cassette style; six speed, constant mesh
Primary drive	22/41
Gear ratio	
First gear:	13/37
Second gear:	16/34
Third gear:	18/32
Fourth gear:	19/30
Fifth gear:	21/30
Sixth gear:	22/29
Final drive ratio	17/43

## ELECTRICAL EQUIPMENT

Voltage	12 V
Alternator	350 W at 5.000 r.p.m.
Battery	12 V - 8.6 Ah

## DIMENSIONS AND WEIGHT

Wheelbase	1.380 mm (54.33 in.)
Overall length	2.015 mm (79.92 in.)
Overall width	760 mm (28.74 in.)
Saddle height	830 mm (32.68 in.)
Min. ground clearance	120 mm (4.72 in.)
Trail	99 mm (3.89 in.)
Dry weight	173 kg (381.4 lbs.) - 165 kg (363.76 lbs)**
Fuel tank capacity	16,5 l (4.36 U.S. gal.)

## PERFORMANCE

Maximum speed*	240.0 km/h (149.1 mph)
----------------	------------------------

## FRAME

Type	ALS Steel tubular trellis
Rear swing arm pivot plates material	Aluminium alloy

## FRONT SUSPENSION

Type	Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload external and separate adjustment
Fork dia.	43 mm (1.69 in.)
Fork travel	125 mm (4.92 in.)

## REAR SUSPENSION

Type	Progressive Sachs, single shock absorber with rebound and compression damping and spring preload adjustment
Single sided swing arm material	Aluminium alloy
Wheel travel	130 mm (5.12 in.)

## BRAKES

Front brake	Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange
Front brake caliper	Brembo radial-type monobloc, with 4 pistons Ø 34 mm (Ø 1.34 in.)
Rear brake	Single steel disc with Ø 220 mm (Ø 8.66 in.) dia.
Rear brake caliper	Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.)
ABS System	Continental MK100 with RLM (Rear Wheel Lift-up Mitigation) and with cornering function

## WHEELS

Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 5.50 " x 17 "

## TYRES

Front	120/70 - ZR 17 M/C (58 W) Pirelli Diablo Rosso Corsa II
Rear	180/55 - ZR 17 M/C (73 W) Pirelli Diablo Rosso Corsa II

## FAIRING

Material	Thermoplastic
----------	---------------

## CONTENTS

Titanium components	Intake and exhaust valves
Exclusive content	Dashboard TFT 5" color display - Cruise control
	Launch control - Bluetooth - GPS - MV Ride App for navigation mirroring, app-controlled engine, rider aids setup - Mobisat tracker
	Chain cover Sup/Low - Air duct covers
	Mudguard rear/front - Lower fairing Right/Left
Carbon components	

## RACING KIT

	Racing 3 exit exhaust system + Dedicated ECU
	Rear seat cover - Customized bike cover - CNC fuel cap (with leather strap) - Certificate of origin - Limited Edition

## EMISSIONS

Environmental Standard	Euro 5
------------------------	--------

\* Top speed attained on closed course.

\*\* RACING KIT with Arrow exhaust and dedicated ECU Map version  
Every country could have a price variation due to local import duties and taxes.